

Remote operation button

P/N: T131171ACC

Copyright

© 2022, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T131171ACC

Commit: 75780

Language:

Modified: 2021-04-20

Formatted: 2022-06-22

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description	
Flic button with Bluetooth for wireless connection to the infrared camera.	
Data communication interfaces	
Bluetooth	Connection to the infrared camera Up to 50 m Bluetooth range
Environmental data	
Radio	FCC ID: 2ACR9-FLIC
Physical data	
Weight	8 g (0.28 oz)
Size (H x D)	8.5 x 30 mm (0.33 x 1.2 in)
Material	PC/ABS with Soft touch coating
Shipping information	
Packaging, type	Cardboard box
List of contents	<ul style="list-style-type: none"> Flic button Metal clip
Packaging, weight	0.068 kg (0.15 lb)
Packaging, size	155 x 59 x 69 mm (6.1 x 2.3 x 2.7 in)
EAN-13	7332558027066
UPC-12	845188023133
Country of origin	Taiwan

Compatible with the following products:

- 79301-0101; FLIR T530 14°
- 79302-0101; FLIR T530 24°
- 79304-0101; FLIR T530 24° + 14°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79305-0101; FLIR T530 24° + 42°
- 79303-0101; FLIR T530 42°
- 79307-0101; FLIR T530 42° + 14°
- 79308-0101; FLIR T530 Dual FOV 14° + 24°
- 79301-0201; FLIR T540 14°
- 79302-0201; FLIR T540 24°
- 79304-0201; FLIR T540 24° + 14°
- 79306-0201; FLIR T540 24° + 14° & 42°
- 79305-0201; FLIR T540 24° + 42°
- 79303-0201; FLIR T540 42°
- 79307-0201; FLIR T540 42° + 14°
- 79308-0201; FLIR T540 Dual FOV 14° + 24°
- 79302-0302; FLIR T540-EST 24°



Remote operation button

P/N: T131171ACC

© 2022, FLIR Systems, Inc.

#T131171ACC; r. 75780;

- 79303-0302; FLIR T540-EST 42°
- 89001-0101; FLIR T560 14°
- 89002-0101; FLIR T560 24°
- 89004-0101; FLIR T560 24° + 14°
- 89006-0101; FLIR T560 24° + 14° & 42°
- 89005-0101; FLIR T560 24° + 42°
- 89003-0101; FLIR T560 42°
- 89007-0101; FLIR T560 42° + 14°
- 89009-0101; FLIR T560 Dual FOV 14° + 24°
- 89002-0302; FLIR T560-EST 24°
- 89003-0302; FLIR T560-EST 42°
- 82501-0201; FLIR T840 14°
- 82502-0201; FLIR T840 24°
- 82504-0201; FLIR T840 24° + 14°
- 82506-0201; FLIR T840 24° + 14° & 42°
- 82509-0201; FLIR T840 24° + 14° & 6°
- 82505-0201; FLIR T840 24° + 42°
- 82508-0201; FLIR T840 24° + 6°
- 82503-0201; FLIR T840 42°
- 82507-0201; FLIR T840 42° + 14°
- 82510-0201; FLIR T840 Dual FOV 14° + 24°
- 89201-0101; FLIR T860 14°
- 89202-0101; FLIR T860 24°
- 89204-0101; FLIR T860 24° + 14°
- 89206-0101; FLIR T860 24° + 14° & 42°
- 89211-0101; FLIR T860 24° + 14° & 6°
- 89205-0101; FLIR T860 24° + 42°
- 89210-0101; FLIR T860 24° + 6°
- 89203-0101; FLIR T860 42°
- 89207-0101; FLIR T860 42° + 14°
- 89212-0101; FLIR T860 Dual FOV 14° + 24°
- 89201-0201; FLIR T865 14°
- 89202-0201; FLIR T865 24°
- 89204-0201; FLIR T865 24° + 14°
- 89206-0201; FLIR T865 24° + 14° & 42°
- 89213-0201; FLIR T865 24° + 14° & 6°
- 89205-0201; FLIR T865 24° + 42°
- 89212-0201; FLIR T865 24° + 6°
- 89203-0201; FLIR T865 42°
- 89207-0201; FLIR T865 42° + 14°
- 89214-0201; FLIR T865 Dual FOV 14° + 24°
- 84502-0301; FLIR E52 24°
- 84512-1201; FLIR E54 24°
- 84512-2102; FLIR E54-EST 24°
- 78511-1101; FLIR E76 14°
- 78512-1101; FLIR E76 24°
- 78514-1101; FLIR E76 24° + 14°
- 78516-1101; FLIR E76 24° + 14° & 42°
- 78515-1101; FLIR E76 24° + 42°
- 78513-1101; FLIR E76 42°
- 78517-1101; FLIR E76 42° + 14°
- 78511-1301; FLIR E86 14°
- 78512-1301; FLIR E86 24°
- 78514-1301; FLIR E86 24° + 14°
- 78516-1301; FLIR E86 24° + 14° & 42°
- 78515-1301; FLIR E86 24° + 42°
- 78513-1301; FLIR E86 42°
- 78517-1301; FLIR E86 42° + 14°
- 78521-2102; FLIR E86-EST 24°



Remote operation button

P/N: T131171ACC

© 2022, FLIR Systems, Inc.

#T131171ACC; r. 75780;

- 78522-2202; FLIR E86-EST 42°
- 90201-0101; FLIR E96 14°
- 90202-0101; FLIR E96 24°
- 90204-0101; FLIR E96 24° + 14°
- 90206-0101; FLIR E96 24° + 14° & 42°
- 90205-0101; FLIR E96 24° + 42°
- 90203-0101; FLIR E96 42°
- 90207-0101; FLIR E96 42° + 14°

Declaration of Conformity

Hereby declaring, under our sole responsibility, that the product:

Product name: Flic, Powered by Flic, Flic 2, Flic Hub, Flic Hub LR

Product number: Flic

to which this declaration relates to is in conformity with the essential requirements and other relevant requirements of the:

- RED (2014/53/EU) replacing outdated R&TTE directive (1999/5/EC)
- EMC directive (2004/108/EC, 2014/30/EC)
- RoHS directive (2011/65/EC)
- REACH regulation (1907/2006)
- WEEE (2012/92/EC)
- Packaging (94/62/EC)

The product is in conformity with the following standards and/or normative documents:

Safety

- IEC 60950-1:2005 (second edition) + A1:2009 + A2:2013
- EN 60950-1:2006+A11:2009+A1:2010+A12:2011 + A2:2013

EMC

- EN 301 489-1 V2.1.1
- EN 301 489-17 V3.1.1

Radio Spectrum

- EN 300 328 v.2.1.1 (2016-11)
- EN 62311:2008

RoHS

- EC50581:2012

Packaging

- EN 13427:2004

Date: 10th January 2020

Stockholm, Sweden

Name: Amir Sharifat

Title: Founder

Signature:


